

IWA 30S + DryDock 18

SPECIFICATIONS

THE GALLEY®

IWA-30-S-DD-18-S-QW



Quartered White Oak / Exclusive Gray Resin+

IWA-30-S-DD-18-S-WA



American Black Walnut / Graphite Resin+

IWA-30-S-DD-18-S-GT



Graphite Wood Composite / Graphite Resin+

IWA-30-S-DD-18-S-GR



Exclusive Gray Resin+ / Resin+

IWA-30-S-DD-18-S-WH



Designer White Resin+ / Resin+


Wash Tools included (WKT-4T)



- (1) Upper Tier Drying Rack
9 1/4" x 18"
DR-09-U-xx
- (1) Lower Tier Wash Caddy
6" x 17"
WC-06-L-xx
- (1) Lower Tier Wash Bowl
12" x 17"
WB-12-L-xx
- (1) Upper Tier Utensil Caddy
6" x 18"
UC-06-U-xx

Upper Deck® & citrine.

Cover set UD-30-18-3P-QW/WA/GT/GR/WH White Oak, Walnut, Graphite, Gray or White Resin



citrine care


- CIT-09-SS-C Stainless Steel Clean + Polish 9 oz
- CIT-17-SS-S Stainless Steel Spray + Refresh 17 oz
- CIT-09-WD-C Wood Condition + Protect 9 oz
- CIT-04-WD-B Wood Finishing Balm 4 oz

Specifications

Single bowl
Users: 1
Wash Tools included: Four
DryDock Tool included: One
Galley BarTap® recommended: One
Outside dimensions: 45 1/2" x 19 1/2" x 2 1/16"
Interior dimensions: 44" x 17" x 2"
Countertop cutout: 44 1/2" x 18"
Minimum cabinet size: 48" or 120cm
Minimum clearance required for DryDock below countertop: 2 1/4"
DryDock location: Drain side (S)

Basin (KSO-30-S-DS-18-S-SS)

16GA 316L stainless steel indoor/outdoor
SilentArmor™ sound reduction technology
Angel finish
Three tier design
Star™ groove pattern
Reversible side drain
Drain cover included
Limited Lifetime Warranty
Made in the USA
ASME A112.19.3/CSA B45.4 certified
cUPC™ certified



Important Installation Note: DryDock requires 2 1/4" minimum clearance below countertop

Customize Your Galley


- Add 7-12" length
- Add 1-6" length
- Add 18" DryDock
- Add 12" DryDock
- Apron front
- 9" depth
- Center drain
- Workstation*
- WorkTop™
- *Color coded labels available

DryDock Tool included (DR-18)



Recommended Basin Accessories & G4

Bottom Grate set BG-30-S-1-SS Stainless Steel



Strainer M-DRN-MSS
Angel Finish 304 Stainless Steel



Disposer Strainer G-DRN-MSS
Angel Finish 304 Stainless Steel



Auto Strainer A-DRN-PSS/MSS/BSS/YSS
Angel Finish 304 Stainless Steel with Polished, Matte, PVD Satin Black, or PVD Brushed Gold knob





Disposal G4-WD-125



SPECIFICATIONS | Right Hand Drain Orientation

Tap Hole Specifications



SUGGESTED GALLEY TAP PLACEMENT GUIDE

Suggested maximum inside corner radius of countertop cutout 3/8"

① Galley BarTap® 1 3/8" min to 1 1/2" max hole diameter

Center Tap hole diameters 2" behind cutout



Note: Galley Hot & Cold Tap requires a minimum 8" clearance to center if installed to the right of the Galley Tap

Note: Tap Placements are for right hand or left hand drain orientation

Call 800.375.4255 or email customer care@thegalley.com
for additional guidance on Tap and Tap Accessory placements

Countertop Cutout Plan

Important Installation Note: DryDock requires 2 1/4" minimum clearance below countertop



STAINLESS STEEL COMPLIANCE ASME A112. 19.3-2008/CSA B45.4-08

WE RESERVE THE RIGHT TO MAKE REVISIONS WITHOUT NOTICE IN THE DESIGN OF PRODUCTS OR IN PACKAGING UNLESS THIS RIGHT HAS SPECIFICALLY BEEN WAIVED AT THE TIME THE ORDER IS ACCEPTED.

DWG and DXF templates available on our website:

TheGalley.com/specification-library



*Questions? For additional assistance, please contact
The Galley's Customer Care Department at 800.375.4255*

IWA 30S + DryDock 18

SPECIFICATIONS | Left Hand Drain Orientation



Tap Hole Specifications



SUGGESTED GALLEY TAP PLACEMENT GUIDE

Suggested maximum inside corner radius of countertop cutout 3/8"

① Galley BarTap- 1 3/8" min to 1 1/2" max hole diameter

Center Tap hole diameters 2" behind cutout



Note: Galley Hot & Cold Tap requires a minimum 8" clearance to center if installed to the right of the Galley Tap

Note: Tap Placements are for right hand or left hand drain orientation

Call 800.375.4255 or email customercare@thegalley.com
for additional guidance on Tap and Tap Accessory placements

Countertop Cutout Plan

Important Installation Note: DryDock requires 2 1/4" minimum clearance below countertop



STAINLESS STEEL COMPLIANCE ASME A112. 19.3-2008/CSA B45.4-08

WE RESERVE THE RIGHT TO MAKE REVISIONS WITHOUT NOTICE IN THE DESIGN OF PRODUCTS OR IN PACKAGING UNLESS THIS RIGHT HAS SPECIFICALLY BEEN WAIVED AT THE TIME THE ORDER IS ACCEPTED.

DWG and DXF templates available on our website:

TheGalley.com/specification-library

Questions? For additional assistance, please contact
The Galley's Customer Care Department at 800.375.4255