Ideal WashStation™ 4S

IWA-4-S-QW



IWA-4-S-WA



American Black Walnut / Graphite Resin+

IWA-4-S-GT



Graphite Wood Composite / Graphite Resin+

IWA-4-S-GR



Exclusive Grav Resin* / Resin+

IWA-4-S-WH



Designer White Resin* / Resin+

Wash Tools included (WKT-4T)



DR-09-U-xx











(1) Upper Tier Utensil Caddy UC-06-U-xx

Upper Deck. & citrine.

Cover set UD-4-2P-QW/WA/GT/GR/WH White Oak, Walnut, Graphite, Gray or White Resin



citrine care

CIT-09-SS-C



CIT-17-SS-S

Stainless Steel Spray + Refresh 17 oz



CIT-04-WD-B Wood Finishing Balm 4 oz

THE GALLEY.

Specifications

Single bowl Users: 1

Wash Tools included: Four

Galley Tap recommended: One

Outside dimensions: 45 1/2" x 19 1/2" x 10 5/16" Interior dimensions: 44" x 17" x 10"

Countertop cutout: 44 1/2" x 18" Basin area: 44" x 16"

Minimum cabinet size: 48" or 120cm

Basin (KSO-4-S-SS)

16GA 316L stainless steel indoor/outdoor SilentArmor™ sound reduction technology Angel finish

Three tier design Star™ groove pattern

Reversible side drain


Drain cover included

Limited Lifetime Warranty


Made in the USA

ASME A112.19.3/CSA B45.4 certified

cUPC™ certified



Center Galley Tap holes 2" from the back of the 18" countertop cutout



Customize Your Galley

Recommended Basin Accessories & G4

Bottom Grate set BG-4-S-2-SS Stainless Steel



Strainer M-DRN-MSS



Disposer Strainer G-DRN-MSS Angel Finish 304 Stainless Stee



Auto Strainer A-DRN-PSS/MSS/BSS/YSS Angel Finish 304 Stainless Ste or PVD Brushed Gold knob















Disposal G4-WD-125

Ideal WashStation™ 4S



Tap Hole Specifications






SUGGESTED GALLEY TAP PLACEMENT GUIDE

Suggested maximum inside corner radius of countertop cutout 3/8"

① Galley Tap 1 3/8" min to 1 1/2" max hole diameter
Center Tap hole diameters 2" behind cutout
Note: Galley Hot & Cold Tap requires a minimum 8" clearance to center if installed to the right of the Galley Tap

Note: Tap Placements are for right hand or left hand drain orientation

Call 800.375.4255 or email **customercare@thegalley.com** for additional guidance on Tap and Tap Accessory placements



STAINLESS STEEL COMPLIANCE ASME A112. 19.3-2008/CSA B45.4-08

WE RESERVE THE RIGHT TO MAKE REVISIONS WITHOUT NOTICE IN THE DESIGN OF PRODUCTS OR IN PACKAGING UNLESS THIS RIGHT HAS SPECIFICALLY BEEN WAIVED AT THE TIME THE ORDER IS ACCEPTED.


DWG and DXF templates available on our website:

The Galley.com/specification-library

Ideal WashStation™ 4S



Tap Hole Specifications




C.O. 18" (457 mm) 1/2" (13 mm) REVEAL FRONT AND BACK 10"(254 I.D. 16" (406 mm)

SUGGESTED GALLEY TAP PLACEMENT GUIDE

Suggested maximum inside corner radius of countertop cutout 3/8"

① Galley Tap 1 3/8" min to 1 1/2" max hole diameter
Center Tap hole diameters 2" behind cutout
Note: Galley Hot & Cold Tap requires a minimum 8" clearance to center if installed to the right of the Galley Tap Note: Tap Placements are for right hand or left hand drain orientation

Call 800.375.4255 or email customercare@thegalley.com for additional guidance on Tap and Tap Accessory placements



STAINLESS STEEL COMPLIANCE ASME A112. 19.3-2008/CSA B45.4-08

WE RESERVE THE RIGHT TO MAKE REVISIONS WITHOUT NOTICE IN THE DESIGN OF PRODUCTS OR IN PACKAGING UNLESS THIS RIGHT HAS SPECIFICALLY BEEN WAIVED AT THE TIME THE ORDER IS ACCEPTED.

DWG and DXF templates available on our website:

The Galley.com/specification-library

Questions? For additional assistance, please contact The Galley's Customer Care Department at 800.375.4255