# Ideal Workstation. 2C

### IWS-2-C-QW



### IWS-2-C-WA



IWS-2-C-GT



IWS-2-C-GR



Exclusive Grav Resin\*

### IWS-2-C-WH



### Culinary Tools included (CKT-12)



UD-12-I-xx





DR-12-U-xx



CB-12-U-xx



P1-12-L-xx



(1) SS

Colander 11" 7.2-qt

C1-11-0-ST



(1) SS Mixing Bowl 11" 7.2-qt B1-11-0-ST

<sup>†</sup> The Upper Deck requires a 1/4" clearance below the surface of the countertop. If the countertop thickness is 3/4" or less, Walnut or White Oak Upper Deck sections will not have the clearance to function above the Upper Tier Culinary Tools.

### Upper Deck. & citrine.

Cover set UD-2-2P-QW/WA/GT/GR/WH White Oak, Walnut, Graphite, Gray or White Resin







(1) 12

Included in CKT

### citrine care

CIT-09-SS-C



Stainless Steel





Wood Condition + Protect 9 oz



### Wood Finishing Balm 4 oz

## THE GALLEY.

### **Specifications**

Single bowl

Users: 1

Culinary Tools included: Five Galley BarTap<sub>®</sub> recommended: One Outside dimensions: 22" x 19 1/2" x 10 5/16"

Interior dimensions: 20 1/2" x 17" x 10" Countertop cutout: 21" x 18"

Basin area: 20 1/2" x 16" Minimum cabinet size: 24" or 60cm

### Basin (KSO-2-C-SS)

16GA 316L stainless steel indoor/outdoor SilentArmor™ sound reduction technology Angel finish


Three tier design Star™ groove pattern

Center drain Drain cover included

Limited Lifetime Warranty

Made in the USA ASME A112.19.3/CSA B45.4 certified

cUPC™ certified



Center Galley Tap holes 2" from the back of the 18" countertop cutout



### Customize Your Galley

### Recommended Basin Accessories & G4

Bottom Grate set BG-2-C-1-SS Stainless Steel



Strainer M-DRN-MSS Angel Finish 304 Stainless Steel

Disposer Strainer G-DRN-MSS Angel Finish 304 Stainless Stee





Auto Strainer A-DRN-PSS/MSS/BSS/YSS Angel Finish 304 Stainless Steel with Polish or PVD Brushed Gold knob














# Ideal Workstation. 2C



### Tap Hole Specifications



1/2" (13 mm ) REVEAL FRONT AND BACK 10"(254 r I.D. 16" (406 mm)

C.O. 18" (457 mm)

### SUGGESTED GALLEY TAP PLACEMENT GUIDE

Suggested maximum inside corner radius of countertop cutout 3/8"

① Galley BarTap- 1 3/8" min to 1 1/2" max hole diameter
Center Tap hole diameters? 2" behind cutout
Note: Galley Hot & Cold Tap requires a minimum 8" clearance to center if installed to the right of the Galley Tap

Call 800.375.4255 or email customercare@thegalley.com for additional guidance on Tap and Tap Accessory placements



### STAINLESS STEEL COMPLIANCE ASME A112. 19.3-2008/CSA B45.4-08

WE RESERVE THE RIGHT TO MAKE REVISIONS WITHOUT NOTICE IN THE DESIGN OF PRODUCTS OR IN PACKAGING UNLESS THIS RIGHT HAS SPECIFICALLY BEEN WAIVED AT THE TIME THE ORDER IS ACCEPTED.

DWG and DXF templates available on our website:

TheGalley.com/specification-library

Questions? For additional assistance, please contact The Galley's Customer Care Department at 800.375.4255